



Specification CR 4410

Pressure espresso and cappuccino coffee machine
A device intended for ground coffee
Pump pressure: 15 bars
Touch panel with 4 buttons: intuitive coffee preparation, hot water and steam generation
Blue indicator light indicates that the coffee is ready to be brewed
Red indicator light indicates that the milk is ready for frothing
Cappuccino system mixes water steam with milk and air to form a cappuccino foam
Heating system ensures a constant water temperature throughout the entire brewing process
Two thermostats precisely maintain the temperature for the effect of perfect coffee 95°C and frothed milk 145°C
3 functions:
- making coffee
- generating steam to froth the milk for cappuccino coffee
- hot water function for drinks, machine cleaning or cup heating
3 programs:
- automatic program for preparing 1 cup of coffee
- automatic program for preparing 2 cups of coffee at the same time
- manual coffee preparation program for any volume
Maximum cup height: 90 mm (+/- 2 mm)
Regulation of steam emission for frothing the milk
Sound signaling the end of automatic programs
Ability to stop the flow of water at any time
Double steel filter extracts the depth of taste and aroma from ground coffee
Two separate steel filters for ground coffee with a capacity adapted to 1 and 2 cups of coffee
Auto shut-off after 25 minutes saves energy
Stainless steel heated desktop for heating cups
Removable transparent water tank 1600 ml
Removable drip tray and frothing nozzle facilitate cleaning
Overheat and overpressure protection
Device dimension: 270 x 234 x 292 mm
Power 850W
Maximum power 1000W
Power supply 220-240V ~50/60Hz
Housing material: Metal
Housing color: Silver
Power cord color: Black
Power cord length: 82 cm
Plug type: E/F

Product availability	531
UNIT EAN code	5902934837644
CTNS EAN code CTNS	
CN code	85167100
UNIT Net weight kg	3.63
UNIT Gross weight kg	4.25
UNIT Size of the box WxDxH	34 x 36 x 28.5
CTN Gross weight kg	4.25
CTN dimensions WxDxH	34 x 36 x 28.5
PACKING: UNIT/CTN	1
PACKING: UNIT/PALLET	40
PACKING: CTN/PALLET	40
PACKING: CTN/LAYER	8
PACKING: LAYERS/PALLET	5

